



REAL TALK

Philippines SRRS 325MHz NTC Two-Way Radio.



Quick Specification:



2.5 watts
RF power



1500mAh
Battery Capacity



16
Channels

Available in:



325Mz
Philippines SRRS

- License Free
- One Time Registration
- Traditional Radio Design



Supplied Accessories



ANTENNA



DESKTOP CHARGER



ADAPTOR



LI-ION BATTERY



BELT CLIP



HAND STRAP



www.cignus.com.ph

PRODUCT SPECIFICATIONS

GENERAL	
Frequency Range	325MHz
Channel Capacity	16
PLL Channel Spacing	5/6.25/10/12.5/25KHz
Battery Voltage	7.4V(Li-ion) 1500mAh
Antenna Impedance	50Ω
Operating Temperature	-20°c_+60°c
Frequency Stability	+2.5PPM
Dimensions (With Battery)	97(H)x58(W)x40(D)mm
Weight (With Battery)	270g
TRANSMITTER	
RF Power Output	2.5w
Modulation Type	F3E
Maximum Deviation	≤5.0KHz(W)
Spurious Emission	≤65dB
Modulation Distortion	≤5%
FM Noise	≤-45dB
RECEIVER	
Circuit Type	Digital Signal Processing
IFs	38.850MHz & 450KHz
Sensitivity (12dB SINAD)	0.2(W)
Squelch Selectivity	0.15(W)
Adjacent Channel Selectivity	≥65dB
Intermodulation	≥65dB
Spurious Rejection	≥60dB
Image Rejection	≥65dB
FM Ham and Noise	≤-45dB
Modulation Type	16KOF3E
Operating Bandwidth	≤+7KHz
AF Output @ 4 Ohms	0.5w
Audio Distortion	≤5%

FUNCTIONS



SCAN



VOX



TOT



CTCSS



DCS

PROGRAMMABLE SIDE KEY

OPTIONS:

- Monitor
- Monitor Momentary
- Scan
- Alarm
- Priority Scan
- Vox